

**Amendments to the Claims**

1. (Previously presented) A process for controlling foaming during an aqueous fermentation process, an aqueous alcoholic fermentation process, or a proteinaceous fermentation process, comprising adding to the process (i) a hydroxy-functional polydiorganosiloxane having a viscosity of 10-150 mPa.s at 25 °C, (ii) a polyglycol with which the hydroxy-functional polydiorganosiloxane is miscible, (iii) a branched silicone resin, and (iv) a silicone polyether.
2. (Currently amended) A process according to Claim 21 including subsequently adding to the process (v) an organic oil composition based on a hydrocarbon oil or vegetable oil.
3. (Currently amended) A process according to Claim 21 including adding to the process (v) a trialkylsilyl-terminated polydiorganosiloxane.
4. (Previously presented) A foam control agent comprising a blend of (i) a hydroxy-functional polydiorganosiloxane having a viscosity of 10-150 mPa.s at 25 °C, (ii) a polyglycol with which the hydroxy-functional polydiorganosiloxane is miscible, (iii) a branched silicone resin, and (iv) a silicone polyether.
5. (Currently amended) A foam control agent according to Claim 24 including (v) an organic oil composition based on a hydrocarbon oil or vegetable oil.
6. (Currently amended) A foam control agent according to Claim 24 including (v) a trialkylsilyl-terminated polydiorganosiloxane.